

WALK-AROUND KOMATSU PC650LC EXCAVATOR

PC650LC-11



Photos may include optional equipment.

NET HORSEPOWER

436 HP @ 1800 rpm
325 kW @ 1800 rpm

OPERATING WEIGHT

140,456–145,284 lb
63710–65900 kg

BUCKET CAPACITY

2.05–4.98 yd³
1.57–3.81 m³

WALK-AROUND KOMATSU 490LC-11 EXCAVATOR

PC490LC-11



Photos may include optional equipment.

NET HORSEPOWER

359 HP @ 1900 rpm
268 kW @ 1900 rpm

OPERATING WEIGHT

105,670–110,220 lb
47,930–49,995 kg

BUCKET CAPACITY

1.47–4.15 yd³
1.12–3.17 m³

**CS433E
CP433E**
Vibratory Soil
Compactors



Stage II Compliant

Cat® 3054C Diesel Engine	
Gross Power	75 kW/100 hp
Compaction Width	1676 mm
Centrifugal Force	
High	134 kN
Low	67 kN
Operating Weight	
CS433E (with ROPS Cab)	6990 kg
CP433E (with ROPS Cab)	7390 kg

CATERPILLAR 966K WHEEL LOADER



VOLVO G710 MOTOR GRADER



FORD F750 WATER TRUCK





Worldwide

English

[Products](#) [Support](#) [Genuine Spare Parts](#) [Industries & Solutions](#) [Discover More](#) [News](#) [Contact](#) [Careers](#)

[Home](#) » [Products](#) » [Power](#) » [Mobile Generators](#) » [G50](#)

G50

Mobile Generators

Information



G50 - Durable mobile generator offers reliable power



The G50 mobile generator offers the perfect power solution where single and three phase power are needed for construction commercial, industrial and special event applications. The sound-attenuated generator provide quiet operation and large fuel tank offers long run times, making it a flexible and reliable choice. A digital controller monitors and protects the generator and engine while providing continuous operating data on an easy to read LCD display.

- Ideally suited for construction sites where durability, reliability and flexibility are required to supply continuous power for applications such as lighting, cranes, concrete mixers and conveyer belts.
- Brushless, oversized alternators with separate excitation winding and AVR (Automatic Voltage Regulation) provide superior motor starting and enhanced ability to run non-linear loads.
- Single switch start and simple, uncluttered control panel provide unmatched ease of use.
- Automatic remote start capability standard which is ideal for temporary standby applications.
- Factory-installed customized options are available. These include, but are not limited to, a fluid containment system, cold weather options, a camlock panel, etc. Also available are optional trailers that are fully equipped and highway ready.

Please note that product availability can vary from country to country. It is possible that information / products may not be available in your country.

These products might also interest you:

Cathodic Protection Test Station - Test site typically 3 feet above grade location fields or ditch crossing



Black mushroom vent cover typically installed behind side walk or best possible location



24" access man hole street application



Test site flush mount grade residential applications





